

FlashAccessory™

MOLDED SEALANT POCKETS

TPO Low Slope Systems

OVERVIEW

FlashCo’s FlashAccessory Molded Sealant Pockets are reservoirs for embedding irregular penetrations and conduit bundles in one-part sealant. The 2” vertical wall creates a perimeter around the penetration while the reinforced TPO flange ties into the existing field membrane. Injection molded with cutting guides at 6 points, FlashCo’s Molded Sealant Pockets provide sizing flexibility on the roof. The two-piece design allows for fast, easy installation by removing the need to disconnect conduits or lines.

INSTALLATION

Sealant Pockets shall be installed in accordance with the recommendations and specifications of the roofing material manufacturer.

1. Prepare all welding surfaces by cleaning with TPO membrane cleaner.
2. Fit both pieces of sealant pocket together around the penetration.
3. If smaller size is required, remove excess material by cutting along vertical guidelines.
4. Heat weld the vertical and horizontal overlaps completely.
5. Heat weld flange to field membrane.
6. Fill sealant with specified sealant (provided by others).

MATERIAL PROPERTIES & CHARACTERISTICS

Material	Thickness	Color
TPO	.060" (60 mil)	White



FEATURES AND BENEFITS

- Save up to 60% of labor
- Waterproof difficult penetrations
- No disconnecting conduits or lines

SAVING THE CONTRACTOR TIME

- FlashCo strives to ship 90% of orders within 1-3 days after purchase orders are placed
- 6 size options to fit multiple size penetrations
- Get off the roof sooner
- Reduce installed costs

STANDARD SIZES & PACKAGING

Opening	Depth	Flange	Quantity	Wt./Box	Box Size
6"x6"	2"	10"x10"	6ea/box	5.0 lbs.	12"x12"x12"
6"x7"	2"	10"x11"	6ea/box	5.0 lbs.	12"x12"x12"
6"x8"	2"	10"x12"	6ea/box	5.0 lbs.	12"x12"x12"
6"x9"	2"	10"x13"	6ea/box	5.0 lbs.	12"x12"x12"
6"x10"	2"	10"x14"	6ea/box	5.0 lbs.	12"x12"x12"
6"x11"	2"	10"x15"	6ea/box	5.0 lbs.	12"x12"x12"
6"x12"	2"	10"x16"	6ea/box	5.0 lbs.	12"x12"x12"

