



Roofnado™ LapLock™ HD60

LapLock™ HD60 surpasses other products in terms of strength and durability, thanks to its 60 mil thickness and five layers of engineered protection, making it ideal for use under all types of tiles, metal, and synthetic roofing. LapLock™ HD60 features GripLap™, our latest lap sealing technology that enhances lap sealing performance and makes installations faster and easier. Not only can LapLock™ HD60 withstand even the most challenging installation environments, but it also excels in walkability, setting it apart from competitors. With proprietary, mechanical, slip-resistant, micro-etched surface technology, LapLock™ HD60 offers enhanced safety, productivity, and performance. LapLock™ HD60 is unmatched when compared to industry-standard, granular, or sand-surfaced ice and water shields. With its rubberized adhesion technology, it provides a strong deck grip and advanced lap sealing, instilling confidence in every installation.

Features & Benefits

- Use under all tiles, all metal panels and shingles, shakes, synthetic shingles, primed cedar shakes and asphalt shingles
- Premium heavy duty construction
- GripLap™ advanced lap sealing technology
- Protection from Ice Dams, Snow, Storms, Water, Hail & Wind Driven Water
- Rubberized adhesion technology for stronger deck grip
- Meets and exceeds ASTM D1970
- Polyset®, Tile Bond™ & Storm Bond adhesives approved
- Texas Department of Insurance approved
- Low temperature flexibility – AC 48 PASS
- Temperature range: 40° F to 240° F
- Limited Lifetime Warranty
- 180 days UV exposure
- Split-release liner
- Custom dual-logo printing available

Test/Standard*

Typical Value

Nominal thickness	60 mils
Weight per square	29 lbs
Permeability ASTM E96	0.027 Perms
Nail Sealability ASTM D1970	Pass
Tensile Strength ASTM D5034	MD 130 lbs (58.96 kg) CD 100 lbs (45.36 kg)
Tear Strength ASTM D1970	MD 75 lbs (34 kg) CD 65 lbs (29.4 kg)
Adhesion to Plywood ASTM D903	4 lbs/inch
Liquid Water Transmission ASTM D4869	Pass
Fire Rating ASTM E108	Class A
UV Exposure	6 Months

HD60's GripLap™ boosts lap sealing performance & makes installs faster and easier!



Roll/Pallet Specs

Length per roll:	67' / 20.4 m
Width per roll:	36" / 0.91 m
Weight per roll:	60 lbs / 27.2 kg
Roll size:	2 sq / 18.58 m ²
Rolls per pallet:	20

*Test data is based on average taken over several production runs and should not be considered or interpreted as minimum or maximum values. Values are typical data and not limiting specifications. All values ± 10 %. This product is manufactured in accordance with national standards which allow for non-critical variances in weights and measures.

†When correctly installed as per installation instructions. All product installation instructions are available to download or view from our website.

LL HD60 SS OCT24

