



## Sahara™ Excel

**Built to Breathe. Built to Last.**


Contractors demand durability—and Sahara™ Excel delivers. Built tough to withstand harsh job sites, unpredictable weather, and extended construction timelines, Sahara™ Excel performs reliably across all climate zones.

Powered by advanced DRYZA™ Smart Nano Technology, Sahara™ Excel breathes from the inside out—allowing trapped interior moisture to escape while creating a robust barrier against wind-driven rain and external water intrusion.

Designed for both contractors and homeowners who understand that a building that breathes is a healthier, longer-lasting one, Sahara™ Excel helps create a drier, more resilient building envelope. It continues to protect long after installation—defending against water penetration while allowing internal moisture to escape.

## Features & Benefits

- DYZA™ Smart Nano Technology
- Advanced breathability creates a drier and healthier building system
- Reactive Extrusion Technology creates a tougher house wrap for busy job sites & rough handling
- Withstands long UV exposure for extended or delayed building projects for up to nine months
- Surfactant resistant construction withstands incidental exposure to hazardous oils, cleaning fluids or power washers
- Limited Lifetime Warranty
- Custom dual-logo printing available



### Test/Standard\*

### Typical Value

Tensile Strength ASTM D5034	MD 72 lbs   CD 57 lbs
Tear Strength ASTM D4533	MD 20 lbs   CD 15 lbs
Permeability (MVTR) ASTM E96B	40 Perms
Basis Weight (ASTM 5271)	115 gsm
Thickness	16 mil
Hydrohead	620 cm H <sub>2</sub> O
Water Holdout ASTM D779	Pass > 60 minutes
Air Leakage ASTM E2178	Pass
Flame & Smoke Spread ASTM E84	Class A
UV Exposure Rating	9 Months

### Available Roll Sizes

Roll width (Ft.)	Roll length (Ft.)	Roll coverage (Sq. Ft.)
3	100	300
3	150	450
9	100	900
9	150	1350
10	100	1000
10	150	1500

\*Test data is based on average taken over several production runs and should not be considered or interpreted as minimum or maximum values. Values are typical data and not limiting specifications. All values  $\pm$  10 %. This product is manufactured in accordance with national standards which allow for non-critical variances in weights and measures.

**Switch to Sahara™ WRBs and start saving on labor, time & money.**  
**Contact us today!**  
[sentrybuilding.com](http://sentrybuilding.com)

SA EXCEL SS SEP25

